



LITELINE 50

Portable Light Line 50m

SPECIFICATIONS ●

LITELINE 50

Model reference	4BDL-050
Dimensions	H200 x W240 x D110
Weight	2.9 Kg
Wire Length	50 meters
Wire diameter	3 mm
Tensile strength	2200 N
Luminance	30 Cd / m ²
Thermal stability	-30°C -70°C
Lithium-Ion Battery	DC 12V / 2.6A
Body Waterproof class	IP55
Flame retardant	UL94 - V0
Charger	220V/110V @ 50/60 Hz
Operation times	Light on mode 170-220 mn Light Blinking mode 1 338-465 mn Light Blinking mode 2 365-555 mn
Battery level indicator	3 LED positions
Brightness control 3 levels	High/Medium/Low
Warranty	2 years

Patent registered in USA, Japan, Korea



CHARACTERISTICS ●

Portable Light Line 50 meters. This equipment is used for firefighter's rescue operations inside a building or at night.

A portable light-emitting evacuation guide lighting line that can mark an escape route so that you can evacuate quickly and accurately in thick smoke and darkness.

Strong tensile strength.

Up to 3.5 hours duration of usage.

Excellent amount of light for visibility.

Battery level indicator.

Light brightness adjustable.

Removable battery for immediate replacement.

3-Step 2-Way signal communication function on flashing visual alarm.

No need to charge for 3 years if not used.