



# LITELINE 52

## Lighting Line for underwater 25m

### SPECIFICATIONS ●

### LITELINE 52

Model reference	4BDL-052
Dimensions	H200 x W138 x D93
Weight	1.3 Kg
Wire Length	25 meters
Wire diameter	3 mm
Tensile strength	2200 N
Luminance	30 Cd / m <sup>2</sup>
Thermal stability	-30°C -70°C
Lithium-Ion Battery	DC 7.2V / 5.2A
Water depth max.	50 meters
Flame retardant	UL94 - V0
Charger	220V/110V @ 50/60 Hz 8.4 V / 1.5A
Operation times	Light on mode 360 mn Light Blinking mode 1 / second 600 mn Light Blinking mode 1 / 2 seconds 600 mn Light Blinking mode 3 / seconds 600 mn
Warranty	2 years

Patent registered in USA, Japan, Korea



### CHARACTERISTICS ●

Personal Light Line 25 meters. This equipment is used for firefighter's rescue operations underwater or at night.

A personal light-emitting evacuation guide lighting line that can mark an escape route so that.

Strong tensile strength.

Up to six hours duration of usage.

Excellent amount of light for visibility in water.

4-Step 2-Way signal communication function on flashing visual alarm.

No need to charge for 3 years if not used.